

# DES - Q42 M

**6 Port 100M PoE Switch with Build-in**

**4\*100M POE+2\*FE RJ45 PoE Switch**



## Introduction


The DES - Q42 M series is a 10/100M un managed PoE switch. It has 4\*10/100M PoE ports and 2\*10/100 Muplink RJ45 ports. Port 1-4 can support IEEE 802.3af/at standard PoE power supply. Port 1-3 single port PoE power reaches 30W, port 4 single port PoE power reaches 60W.

The maximum PoE output power is 65W. As a PoE powersupply device, it can automatically detect and recognize the power receiving equipment that meets the standard and supply power through the network cable. It can supply power to POE terminal equipment such as wirelessAP, web cam, VoIP, visual intelligent building intercom through network cable, and meet the network environment thatneeds high-density PoE power supply. It is suitable for hotel, campus, factory dormitory and small and medium-sized enterprises.

# Highlights

- ☆ 4\*10/100M + 2\*100M RJ45 Port PoE Switch, 1-4 ports support IEEE802.3af/at;
- ☆ Comply with IEEE 802.3, IEEE 802.3u standards;
- ☆ Support AI Watchdog, Port self-healing, VLAN, extend 300 meter distance, Auto Speed Change, Priority port & reduce the after-resale;
- ☆ PoE port support AF/AT intelligent recognition. Standard power is 15.4W/port, port 1-3 Maximum power:
- ☆ Supports POE devices such as wireless access points (APs) and network surveillance cameras through Category 5/6 Ethernet cables;
- ☆ The power supply total is 65W;
- ☆ 2 years warranty.

## DIEMENSION



# Technical Specification-

MODEL	DES - Q42 M
Fixed Port	4*10/100Base-T/TX PoE ports (Data/Power) 2*10/100Base-T/TX Uplink RJ45 ports (Data)
POE Port	Port 1-4 support PoE
Feature	With the Dial code switch, support port priority by default.  E: AI Extend 300meters transmission and auto speed change of single port (limit 10Mbps), other ports maintain 100M/1000M within 100 meters;  V: Turn on, 1-4 Port support each port Isolation & VLAN;  D: Turn on, 1-4 Port support AI-PoE Network self-healing mode (PoE Watchdog function), Automatic solve the camera problem & reduce after-sale.
Network Protocol	IEEE802.3 10BASE-T; IEEE802.3i 10Base-T; IEEE802.3u 100Base-TX; IEEE802.3x.
Ethernet Port Feature	10/100Base-T(X) automatic detection, full/half Duplex MDI/MDI-X adaptive
Fiber Port Feature	Store and Forwards
Switching Capacity	1.2Gbps
Forwarding Mode	0.89Mpps
MAC	2K
Buffer Memory	768K
Twisted Pair Transmission	10BASE-T:Cat5 UTP(≤300 meter) 100BASE-TX:Cat5 or later UTP(≤100 meter)
Power Supply Pin	Default 1/2(+), 3/6(-);
MAX / AVERAGE Power Per Port	<b>Port 1-3 30W/15.4W, Port 4 60W/15.4W</b>
Total PWR / Input Voltage	65W (52VAC)
Power Consumption	Standby:<2W;Full load:<65W
LED Indicator	Power indicator: PWR (Green);  Network indicator: 1-4(Link/Act)/ (Green),5-6(Link/Act)/ (Green),
Power Supply	Build-in power adaptor AC100~240V 50-60Hz,65W
Operation TEMP / Humidity	-20~+55°C:5%~90% RH non condensing
Storage TEMP / Humidity	-40~+75°C:5%~95% RH non condensing
Dimension	195*130*40mm
Net /Gross Weight	<0.8kg / <1.2kg
Installation Method	desktop type, wall mounted

Protection	IEC61000-4-2(ESD): ±8kV contact discharge, ±15kV air discharge IEC61000-4-5(Lightning protection/Surge): Power:CM±4kV/DM±2kV; Port: ±4kV
Protection level	IP30
Certification	CCC;CE mark, commercial;CE/LVD EN60950; FCC Part 15 Class B;RoHS
Warranty	2 years, lifetime maintenance.

## Applications-



### PACKING LIST

CONTENT	QTY	UNIT
6 Ports 100M PoE Switch with build-in DES - Q42 M	1	SET
User Guide	1	PC
Warranty Card	1	PC