

ENTRY LEVEL IP PHONE



DXP 3000 / 3000P











DXP-3000 TECHNICAL SPECIFICATIONS

Basic Functions	2.3"132*64px graphical LCD screen with a 7-adjustable brightness level on the backlight, 2 SIP accounts, Call Forward, Call Transfer, Call Waiting, Hotline, Call Hold, Auto Answer, Redial, Mute, DND, Local 3- Way Conferencing, Speed Dial, Voice Mail, Local Phonebook (up to 2000), Direct IP call without SIP proxy, Black list, Dialed/Received/Missed/Forwarded call (400 total), Call Center Headsets mode.
Shortcut functions	7 Function keys: message, headset, transfer, mute, redial, hands-free speakerphone, 4 Soft keys, 4 navigate keys, volume+/- .
IP PBX Feature	Intercom, Paging, Call pickup, Call park, Anonymous call, Anonymous call rejection, Hold on music, Conference Call, Group pickup, DND & Call forward state synchronization, Call Recording.
Multi-language	English, German, Italian, French, Spanish, Portuguese, Russian, Simplified or Traditional Chinese, Polish, Turkish, Hebrew.
Advanced Features	LDAP, XML remote phonebook, Action URL, Active URI, CSTA, Multicast paging.
Audio Features	5 ringtones (system ringtone or custom ringtone) article, 8 volume adjustable & Mute mode, Narrow-band codec: G.711(a/μ), G.729A/B/AB, G.726, iLBC, OPUS, Wideband codec: G.722, L16, Support VAD, CNG, AEC, PLC, AJB, AGC, Full-duplex speakerphone with AEC.
Network Feature	Static IP and DHCP, IPv4 /IPv6, Dual stack IPv4/IPv6, ARP/RARP, DNS A/DNS SRV/DNS NAPTR LLDP/CDP/DHCP VLAN; IEEE802.1X; OpenVPN; DSCP, 802.1p QoS; SSL Time and Date Synchronization: SNTP, PBX, DHCP, Transport: UDP/TCP/TLS; RTP/RTCP/SRTP, QoS: Layer 3 (ToS, DiffServ).
Security	TLS, HTTPS, SRTP (RFC3711), Digest authentication using MD5/MD5-sess, AES encryption for configuration files, Phone lock, The administrator/user level access control.
Management	Configurable through web interface/phone.
Auto-provision	Service (RPS), TR069, Import/Export CFG file via web, Generate multiple configuration files via tool, Periodic check and update.
Physical	New stand, wall mountable, AC/DC adapter, AC input: 100~240V, 50~60Hz > DC Output: 5V, 0.6A Power consumption (PSU): 0.87~1.18W, > Power consumption (PoE): 0.72~1.78W, Dimension (W x x H) 200mm × 165mm × 47mm.
Keys Feature	Mute, Redial, Headset, Hands-free), 1 Multi-scene key.
Temperature & Humidity	Relative humidity: 10%90% (No Condensing), Operation temperature:0~45°C.
Package	Qty/CTN: 10 PCS, N.W/CTN: 7.5 kg, G.W/CTN: 9.47 kg, Giftbox size: 288mm × 217mm × 60mm, Carton size: 448mm × 320mm × 302mm.
Certifications	CE: EN60950, EN50332, EN300328 V1.9.1 FCC: Part15, Part15.247
PBX Compatibilit	Zycoo Broadsoft Asterisk Elastix Trixbox Freeswitch Huawei Avaya Mitel Unify ZTE Etc.

WHY CHOOSE DXP-3XXX SERIES

The DXP-3XXX series is a dual port fast Ethernet IP phone with 2 SIP accounts and 2-line buttons. Its 2.3"132*64px graphical LCD screen with a 7-adjustable brightness level on the backlight, HD speaker, simple fixed buttons, unique appearance and exquisite details” bring customers higher work efficiency and user experience. It is a cost-effective economical IP phone specially designed for office. It supports IPV6 and IPV4, with full "user, network, deployment, security" feature and good IPPBX and network compatibility. Its suitable for enterprise unified communications and operator cloud voice. Its innovative multi-scene usage mode greatly enhances the work efficiency of economical IP phones.

-  Personalized multi-scenario usage mode. Users can set the button mode according to the usage requirements and habits, which sets a new efficiency benchmark for the entry-level phone.
-  More convenient operation by adding the usage help information.
-  Higher level voice quality by using sealed electroacoustic cavity and high-level electroacoustic devices. Excellent hands-freevoice quality with larger HD speaker. Full view screen. OPUS codec supported.
-  OPEN VPN, LLDP and 802.1X supported.
-  Anti-electromagnetic feature on handset and speaker, such as mobile phones.
-  Power protection measures to avoid machine damage caused by wrong operation.
-  Convenient deployment, support auto provision via WAN and LAN.
-  Perfectly compatible with leading IP PBX platform and third-party interface management supported.

	DXP-3000	DXP-3000P
PoE	N	Y
100m	Y	Y

